

	Multi-Use	Single-Use	Internal Sensor	External Sensor	4,000 Logs Memory	8,000 Logs Memory	16,000 Logs Memory	User Configurable	Cradle Required	USB Connector	Display	Fixed Battery	Replaceable Battery	5V via micro USB socket	Temperature Range	Ultra-Low Temperature Range	Audible Alarm	Multiple Alarm	Temperature & Humidity	WiFi	PDF Report
Data Logger																					
TRIX-8	✓		✓			✓		✓	✓			✓			-40°C to +85°C						
TRIX-16	✓		✓				✓	✓	✓			✓			-40°C to +85°C						
TREX-8	✓			✓		✓		✓	✓			✓			-40°C to +99°C						
TRID30-7R	✓		✓			✓		✓	✓	✓			✓		-30°C to +60°C						
TRID30-7F	✓		✓			✓		✓	✓		✓	✓			-30°C to +60°C						
TRIL-8	✓		✓			✓		✓	✓			✓				-80°C to +40°C					
TREL-8	✓			✓		✓		✓	✓			✓				-80°C to +40°C					
TREL30-16	✓			✓			✓	✓	✓		✓		✓			-80°C to +40°C	✓				
TRED30-16R	✓			✓			✓	✓	✓		✓		✓		-40°C to +99°C		✓				
UTRIX- 16	✓		✓				✓	✓		✓		✓			-30°C to +70°C			✓			✓
UTRID-16	✓		✓				✓	✓		✓	✓		✓		-30°C to +60°C			✓			✓
HAXO-8	✓		✓			✓		✓	✓			✓			-40°C to +85°C				✓		
vaxtag	✓		✓			✓			✓		✓	✓			-30°C to +60°C						
UTRED30-16	✓			✓			✓	✓		✓	✓		✓		-40°C to +99°C		✓	✓			✓
UTRED30-WIFI	✓			✓			✓	✓		✓	✓		✓	✓	-40°C to +99°C		✓	✓		✓	✓
UHADO-16	✓		✓				✓	✓		✓	✓		✓		-30°C to +70°C		✓	✓	✓		✓
SRIC-4		✓	✓		✓			✓	✓			✓			-30°C to +60°C						
SRIL-8		✓	✓			✓		✓	✓			✓				-80°C to +40°C					
USRIC-4		✓	✓		✓			✓		✓		✓			-30°C to +60°C						
USRIC-8		✓	✓			✓		✓		✓		✓			-30°C to +60°C			✓			✓
HASO-8		✓	✓			✓		✓	✓			✓			-40°C to +85°C				✓		
USRID-16		✓	✓				✓	✓		✓	✓	✓			-30°C to +60°C						✓
Temperature Indicator																					
TIC 20		✓	✓								✓	✓			-30°C to +60°C				✓		
TICT		✓	✓								✓	✓			-25°C to +60°C				✓		
iSOTag		✓	✓								✓	✓			-25°C to +60°C						