

# Release Notes for LogTag® Analyzer 3

## 3.1 release 6

### **New Features**

- UHADO-16 / HASO-8: Added support for the new data loggers.
- LogTag Online: Integrated LogTag Online functionality with Analyzer. Integrated ability to Register, upload, and view data from supported logger with the LogTag cloud.

### **Bug fixes:**

- All Loggers (except Vaxtag): Added option to view and print a calibration certificate for loggers manufactured after April 2019. Available as a button from the logger configuration window, or the Report tab when viewing a file or downloaded logger.
- All Loggers: In File – Properties, corrected the “Data originally acquired” field. In some cases this could use the wrong time zone.
- All USB Loggers: Improved robustness to recover from logger memory corruption. There will be fewer instances of corrupt calibration errors.
- All USB Loggers: Allow unicode characters in USB/PDF logger description field to allow localized content (Note: Unicode characters are not currently supported by USB logger firmware, so PDF files generated may contain unrecognizable characters).
- USRIC-4 (firmware version 4.02.01 or earlier): Add “push button start from hibernation” start mode to allow start delay to be configured and used. Use this mode instead of standard push button start, as this firmware may start immediately even if start delay is configured in standard push button start mode.
- USRIC-4 (firmware version 4.02.01 or earlier): When start delay is configured, automatically set to “Push button start from hibernation” and disable pre-start logging. This works around an issue in these firmware versions. Corrected in later USRIC-4 firmware versions.
- USRIC/UTRIX/UTRID: Corrected statistics for zoomed values for USB multi-alarm loggers.
- TRIL/SRIL/TREL: These loggers can no longer be configured together or with each others profiles. This avoids unexpected results during configuration.
- TRID/TRED: Upper and lower alarm thresholds now use more accurate values. This prevents readings reported as acceptable to trigger an alarm and vice versa.
- HAXO-8: Corrected behaviour where in rare circumstances an extra fictitious reading would be shown.
- Several improvements to File-Open and File-Save behaviour where a non-existent or invalid file path is used.
- Use correct decimal place symbol throughout LogTag Analyzer (e.g. comma ‘,’ or period ‘.’) as defined by the local PC region settings, including for the exported files (CSV, HTML etc...).
- All USB Loggers: The brand name displayed on the on-board PDF report and in the file names is now as intended.

## 3.1 release 5

- Added Data view for Multi-Charts with up to 10 files.
- Added French Language for selection.
- A configuration profile issue for USRIC-4 loggers has been resolved.
- Corrected the number of starts displayed in Report for multi-use loggers.
- Aligned data list display of alarm readings with LogTag® Analyzer version 2.
- Corrected chart display of sensor disconnected readings for TREX-8 and TREL-8 loggers to match the display of LogTag® Analyzer version 2.
- Updated the Set Timezone method for Vaxtag® loggers.
- Corrected various issues when importing and exporting option settings.
- Aligned HAXO-8 low battery display with LogTag® Analyzer version 2.

## 3.1 release 3

- Load battery test during ambient temperature has been changed to allow TRIL configuration.

## 3.1 release 2

- This release corrects an issue where, in some cases, temperature loggers that were adjusted using LogTag Calibrate showed incorrect values near both ends of the product's temperature range.

## 3.1 release 1

- Corrected download push button start with no start delay configuration Update imported profiles to show correct start delay in edit profile dialog. Corrected issue with temporary files that caused non-admin user being unable to open .ltd files with Explorer double-click.

## 3.1 release 0

- Added support for new products TREL30-16, UTRED30-WIFI and UTRED30-16
- Added SFTP protocol for file upload
- Sending emails: Added support for Office365 mail servers
- Added support for user resettable Min/Max, including chart displays and Report Event info
- Added information about unsupported configuration settings when using configuration profiles or configuring multiple LogTags together
- Improved Hibernate function
- Improved display markers for re-calibrated readings for USB-LogTags
- USB LogTags: Configuration now always enables the "Prioritise download over file generation"
- HAXO chart: Show correct x-axis labels for humidity chart when temperature chart is disabled
- Re-set HAXO re-calibrated markers on configuration
- Improved options import/export
- Improved Report and PDF Report layout for languages German, Spanish and Russian
- Improved PDF export: Removed empty pages, improved receiver notes, page number positions

- Improved display of sensor disconnected readings in file exports
- Corrected diagnostics email settings that lead to rejection of support emails sent from Gmail accounts
- Improved handling of page margin units in Page Setup dialog
- Corrected "Push button start from Hibernation" setting in profile
- Corrected total log duration calculation in Configuration Log
- Corrected Auto-download button behaviour according to configuration
- Improved overall stability of the application
- Fixed program freezing issue with Analyzer when a computer exited sleep mode
- Themes are no longer supported
- Fixed a bug with the 3.0r8 installer where additional user accounts are prompted to run the installer again to verify files.

## 3.0 release 8b

- Fixed a bug with the 3.0r8 installer where additional user accounts are prompted to run the installer again to verify files.

## 3.0 release 8

- Fixed bug where beeper was incorrectly shown when creating USB logger profiles.
- Added apply zoom to all charts feature when Manually Scaling.
- Improved diagnostic email system to still allow sending if no mail client is available on PC.
- Added shift chart functionality in Multi-Chart.
- Profiles now handle new lower limits for SRIC-4 and UTRID-16 products.
- Changed minimum alarm separation between Upper and Lower alarms from 1 degree to 0.1 degree.
- UTRIX-16 and UTRIX-16M configuration has been merged to allow both to be configured at the same time.
- USRIC-8 and USRIC-8M configuration has been merged to allow both to be configured at the same time.
- Average chart is now regenerated when a range change occurs.
- Added Fast Start configuration for loggers which support it.
- Added native support for Gmail in SMTP server settings.
- Upgraded to .NET version 4.6.1 to support Gmail.
- Added support for the up and coming HID Interfaces.
- Fixed bug with profiles where the number of readings were limited for TRED-16, USRIC-16 and TRIX-16.
- Fixed bug when creating reports that the Chart Image was sometimes not displayed.
- Fixed bug where printing sometimes created reports without charts.
- Fixed bug where sometimes files would not open due a perceived file permissions error.
- Fixed bug where Chart Range Select control was enabled when in Average Chart Mode.
- Fixed bug where the path in the folder starting with '\\\' was being converted to \'\' when the folder was saved.
- Enabled saving Multi Chart files containing .sltd files
- No correctly disables annotate chart mode when leaving a Multi Chart tab.
- Corrected a crash when prompting for logger password during configuration with profile.
- Profile name changes are now saved.

- Fixed a bug when trying to save files without extensions crashed Analyzer.
- Fixed not being able to set a Download Password for the UTRID-16 LogTag.
- Corrected bug where default document display settings for zooming to Marks was displaying inconsistent charts.
- Corrected bug where download mark on last reading and default display set to last mark last reading would sometimes crash analyzer.
- Fixed showing marks on the latest model TRED30-16R graphs.

## SDK 3.0.8

- Support for Check digits in Interfaces and products with serial numbers that start with an alpha character.
- Increased accuracy Battery Test implemented for SRIL-8 and TRIL-8 products.
- Fixed bug where trying to configure a newer TRIL/SRIL would cause a comms error to be returned.
- Added support for the up and coming HID Interface.
- UTRIX-16M and USRIC-8M with firmware versions  $\geq 6.6.1$  now return logger model name without "M".
- Fix to correctly set older HAXO firmware Humidity alarm alert values which were causing incorrect red LED behavior.
- Updated NextStart date/time member of ProductInfo for USB loggers to be in Configure Timezone and not UTC.
- Fixed bug where clock change flag was not being set in the reading when found (TRID/TRED).
- Added a wait for user server reply when user server is running on the local PC.

## 3.0 release 7

- Fixed bug where Range Selection was re-enabled after the tab was changed even when there were only started or pre-start readings.
- Fixed bug with some files being generated were incompatible with LTA 2.x
- Fixed zooming bug when less than 2 started or 2 pre-start readings and changing chart range.
- Fixed bug when displaying a multi-chart report with some series turned off the chart image would not be generated.
- Corrected Alignment issues, Chart and Chart Menu display with non-English languages.
- fixed functionality for 'Reset all documents to selected options' in Options -> Charts when the checkbox is not checked.
- Fixes to Report to ensure all DateTimes using settings from Options -> Date and Time.
- Fixes to Report where the logo image was sometimes not displayed.
- Fixed Email validation, where sometimes recipient email addresses were not being correctly validated
- Fixed bug where adding a new window before saving a multi-chart could cause a crash.

## SDK 3.0.7

- SDK change for TRED30-16R configuration: Clear beeper status on configuration for firmware version 5.2x

## 3.0 release 6

- Changed the main menu to truncate long foreign words in order to avoid Icon buttons growing too large
- Fixed Report to cater for long translated terms.
- Fixed Multi-Chart Report Start and Finish times.
- Fixed Rendering for non validated series under certain conditions.
- Added Help file topic links and F1 support to the various forms
- Added TRED30-16R support to TRID\_TRED profiles.
- Save file open path when opening documents so is not lost on Analyzer close.
- Added specific readings compare for stopped loggers download so support auto-saving re-calibrated loggers.
- Fixed profiles so alarm temperatures are converted between different Temperature ranges.
- Added Max readings option to profiles.
- Fixed bug where email generated by clicking SendMail did not wait for PDF generation to complete if the file was not already present.
- Fixed Bug where Saving a document over another document that was currently open could cause Analyzer to crash.
- Fixed scaling bug with Chart when disconnected readings are present.
- Fixed bug where reading marks were being shown on Invalid readings.
- Fixed bug where Windows List Separator for csv export was actually using selected language List Separator.
- Fixed bug where font styles were not being displayed in the annotations dialog.
- Fixed bug where email generated by clicking SendMail did not wait for PDF generation to complete if the file was not already present.
- Fixed download bug with USB LogTags where a download could sometimes cause the program to stop responding.
- Fixed download bug where a file would be displayed automatically even if the option was not selected, if no new file was being created.
- Added Manual Scaling by Index to Chart Manual Scaling.
- Added Print All functionality

## SDK 3.0.6

- Fixed bug where Calibration Checksum was not recalculated after clearing the re-calibrated readings flag on configure.
- Added fall-back to Start Log Time when Last Log time is corrupted for USB products.
- Added support for new version USRIC-4.
- Added support for LogTag Wifi Interface generated ltd files.
- Added Tadiran loaded battery test support on device Configuration.
- Updated HAXO 2.2 battery voltage calculation to provide actual voltage instead of pass/fail
- Added fix for Hibernating USB products with DateTime start, sets to Push Button Start
- Added Support for USRIC-16

## 3.0 release 5

- Added Support for UTRID-16, UTRIX-16M, and USRIC-8M LogTags.
- Added Support for the TRID30-16R.

- Added profile support for new products.
- Added viewing of, and configuring with, ReadOnly profiles.
- Added Russian, German and Spanish Language Support.
- Added Prioritize Download option to the configuration of USB LogTags.
- Added support for pdf timezone display for USB pdf LogTags.
- Added additional warning messages and increased error message support.
- Increased performance for rendering charts with many readings in Single Chart mode.
- Better Support for Windows scaling for high resolution displays.
- Fixed several bugs to do with creating, editing and applying profiles.
- Updated the wizards to use progress bars.
- Fixed several bugs which could cause Analyzer to crash under unusual circumstances.
- Fixed USB LogTags communications on Windows 10.
- Modified various dialogs so they remain on top until actioned.
- Fixed some bugs in statistics generation for several unusual circumstances.
- Fixed Alarm state for reports with zoomed readings to only calculate state off the zoomed readings.

## SDK 3.0.5

- Added Support for UTRID-16, UTRIX-16M, and USRIC-8M LogTags.
- Added Support for the TRID30-16R.

## 3.0 release 3

- Added Configuration Profiles, creation, import, export and read-only.
- Added Configure LogTags from Profile.
- Added create profile from current logger settings in configure dialog.
- Added option to retain Password/UserID during configuration.
- Linked Temperature and Humidity Clear Alarm Checkboxes when configuring a HAXO-8.
- Renamed User ID to Description.
- Restricted Description field for USB loggers to 50 characters to retain usability with Generated PDFs.
- Added display of Preset specified maximum trip length in days.
- Updated USB Download Password checkbox so when enabled, removes the file settings tab.
- Fixed result displayed when downloading Indicator products using Download and Wizard.
- Added code to manually and automatically check for updated versions of LogTag® Analyzer.
- Added ability to automatically download and install newer versions of LogTag® Analyzer.
- Displays important details about upgrade within the Check for Updates Window.
- Added ability to export Day Summary as a second file when exporting an ltd into a text format.
- Can now Export a TICT or TIC20 into a text format and it will export the Day Summary table.
- Fixed some bugs in statistics generation for some alarm counts with delayed alarms.
- Using SendMail command will now create additional exported files if they are not already present.
- Added saving ltd data into exported PDF files.
- Updated UI to fix bugs caused by Windows Scaling be greater than 100%.
- Some fixes to Themes within LogTag® Analyzer, others removed.



- Some changes to Icons and images within LogTag® Analyzer.
- Corrected line thickness for Average Multi-Charts.
- Added escape key functionality to close many of the forms.
- Added processing dialog for multi-chart operations to indicate program activity.
- Added opening of PDFs which contain ltd data (LogTag® Analyzer and USB logger PDFs).
- Fixed bug with Multi-Chart displaying Paused Marks for USB Pause readings.
- Changed Temperature/Humidity alert range from checkbox to toggle button.

## SDK 3.0.3

- Fixed bug with TRID when Temperature was an exact match to the top calibration table value.
- Updated SDK to assume a log interval of 1 minute if the log interval value is 0.
- Added EvenInterval flag to HAXO-8 to restrict log interval to even seconds.
- Added recovery code for readings if clock has become corrupted after primary logging has commenced.
- Updated SDK to support Prototype TRIX-8 files/units which do not have a SensorID recorded.
- Correctly write new checksum when a battery de-rate is carried out.
- Fixed iS0°Tag code to correctly detect when the unit is still logging.

## 3.0 release 2

- Chart Control Panel now uses check boxes instead of buttons.
- Chart Control Panel can now be shown or hidden. The default can be set in Options – General Settings.
- Hide Logon/Logoff button on Menu if User Server is not set up.
- Removed bold text when menu items are disabled; increased text size for readability.
- Updated Menu to hide unused overflow buttons, updated control intelligence depending on document and program state, also updated Chart Control Panel with same functionality.
- Theme changes to LogTag® Analyzer, new icons and images, added various colour changes to text.
- Updated default chart colour palette to be different from initial custom chart colour palette.
- Updated Black Theme with many fixes for Dark Text, background colours, corrected some image issues.
- Added option to preserve a LogTag®s description/password to the configuration dialogue and the wizard.
- Updated configuration dialogue to hide the password entry field if not enabled via one of the checkboxes.
- Fixed bug with export format for exporting a LogTag® with only prestart readings.
- Updated configuration dialogue to disable number of readings control if wraparound selected.
- Added automatic adjustments to the ‘Days’ configuration control.
- Removed sliders for configuration of days and readings.
- Fixed bug with configuring only accumulative alarms with some models.
- Added basic information to file properties for multi-chart files.
- Fixed delays and periods of non-responsiveness when closing and opening wizard forms.
- Fixed “Not Found” on first open of wizard form when previous form was closed in the middle of an operation.
- Modified HTML export format to use visually formatted tables for exports.

- Added configure and download logging functions for logging data including several new fields. Changed all logging functionality to point to a combined log folder.
- Added ability to view saved log files (config, download) in HTML formatted tables (With Save As and Print buttons).
- Fixed bug with displaying email options in Options – Automation.
- Added UTF-8 encoding marker bytes to start of text files.
- Fixed custom scale range to appear relative to settings window. Fixed some bugs with custom scaling and chart range scaling boundary conditions with controls.
- Added Import and Export functions for the option settings via the .asxml format
- Fixed bug with Validation of date & time Settings in Options – Date and Time where certain selections were not working correctly.
- Enabled Zoom Out functionality with Data Tab displayed.
- Updated text annotations to be multi-line via Enter when editing.
- Document page tabs now have bold text to improve tab visibility.
- Fixed bug with Auto-Save and Multi-chart Save As interactions.
- New documents now have their tab added to right side and are brought to the front.
- Report notes and print preview windows no longer open as topmost panels.
- Updated TICT and TIC20 rounding for maximum and minimum temperatures for negative values to match display.

## SDK 3.0.2

- Added new EXTRA flag for even second clock limitations to the SDK which is used to indicate when the firmware requires an even seconds interval.
- Added more recovery Checks in SDK to try and correct and display data from corrupted loggers and truncated memory reads.
- Fixed bug with time calculation function for iS0°Tag products in SDK.
- Added USB Port re-enumeration function to SDK when FTDI USB Interface stops responding.
- Updated LogTag® Analyzer to handle USRIC-4, USRIC-8 and UTRIX-16 products, display PDF time zone date-times when Configuration Display Time Zone is selected.
- Added Mass Storage Hold-Off support for future USB products.